

RECEIVED
CENTRAL FAX CENTER
MAY 17 2007

60,010-074; H2678-SS

IN THE CLAIMS

1.-6. (Cancelled)

7. (Currently Amended) ~~The~~ An electrochemical cell structure comprising of Claim 6,
further comprising

a first fluid chamber;

a resilient member comprising an uncoiled wave spring disposed in said first fluid
chamber, wherein said uncoiled wave spring is metallic and comprises a first peak, a
second peak and a valley spaced between said first peak and said second peak;

an opening for permitting communication of a fluid into said first fluid chamber
from one of an anode cavity and a cathode cavity; and

a second uncoiled wave spring located concentrically with said uncoiled wave
spring.

8. (Currently Amended) The electrochemical cell of Claim 4-7 wherein said resilient member is electrically conductive.

9.-10. (Cancelled)

11. (Currently Amended) The electrochemical cell of Claim 4-7 including a second resilient member positioned within a second fluid chamber, said second fluid chamber in fluid communication with said one of an anode cavity and a cathode cavity and said first resilient member in fluid communication with the other of said one of an anode cavity and a cathode cavity.

12. (Previously Presented) The electrochemical cell of Claim 11 wherein said first resilient member is biased to apply a first spring force in a first direction and said second resilient member is biased to apply a second spring force in a second direction opposite to

60,010-074; H2678-SS

said first direction.

13. (Cancelled)

14. (Currently Amended) ~~The~~ An electrochemical cell structure comprising: ~~of Claim 13~~

a spring; and

a spring frame for positioning said spring relative to an electrochemical cavity wherein said spring frame has a side facing toward said electrochemical cavity and another side facing away from said electrochemical cavity and at least one spring frame opening that extends between said sides for receiving said spring and permitting fluid flow between said sides, wherein said spring frame opening comprises a plurality of ribs.

15. (Previously Presented) The electrochemical cell of Claim 14 wherein each of said plurality of ribs extends generally radially from a center of said spring frame.

16. (Currently Amended) The electrochemical cell of Claim ~~13-14~~ wherein said spring comprises a wave spring having a first peak, a second peak and a valley spaced between said first peak and said second peak.

17. (Currently Amended) The electrochemical cell of Claim ~~13-14~~ wherein said spring comprises a first circular spring and a second circular spring, said first circular spring generally concentric with said second circular spring.

18. (Currently Amended) The electrochemical cell of Claim ~~13-14~~ wherein said spring and said spring frame are electrically conductive.

19.-20. (Cancelled)

60,010-074; H2678-SS

21. (Currently Amended) ~~The~~ An electrochemical cell structure comprising of Claim 20 wherein

a spring; and

a spring frame for positioning said spring relative to an electrochemical cavity wherein said spring frame has a side facing toward said electrochemical cavity and another side facing away from said electrochemical cavity and at least one spring frame opening that extends between said sides for receiving said spring and permitting fluid flow between said sides, wherein said at least one spring frame opening comprises an annular channel and said annular channel comprises a plurality of ribs spaced circumferentially within said annular channel.

22. (Previously Presented) The electrochemical cell of Claim 21 wherein said spring is interlaced among said plurality of ribs such that said spring passes alternately over and under said plurality of ribs to resist circumferential movement of said spring relative to said spring frame.

23. (Currently Amended) ~~The~~ An electrochemical cell structure comprising of Claim 6 a first fluid chamber;

a resilient member comprising an uncoiled wave spring disposed in said first fluid chamber, wherein said uncoiled wave spring is metallic and comprises a first peak, a second peak and a valley spaced between said first peak and said second peak, and wherein said uncoiled wave spring is an annular structure, and the first peak, the second peak, and the valley extend out of a plane of the annular structure;

an opening for permitting communication of a fluid into said first fluid chamber from one of an anode cavity and a cathode cavity.

24. (Currently Amended) The electrochemical cell of Claim 13 ~~14~~, further comprising a separator plate adjacent said spring frame and moveable relative to said spring frame.